



(NSK) 6030 CM Bearing

Bearing No. 6030

6030 Bearing 2D drawings and 3D CAD models

Size	150x225x35 mm
Bore Diameter	150 mm
Outer Diameter	225 mm
Width	35 mm
d	150 mm
D	225 mm
B	35 mm
C	35 mm
r min.	2,1 mm
da min.	161 mm
da max	170 mm
Da max.	214 mm
ra max.	2 mm
Weight	4,24 Kg
Basic dynamic load rating (C)	126 kN
Basic static load rating (C0)	126 kN
(Grease) Lubrication Speed	2 600 r/min
(Oil) Lubrication Speed	3 000 r/min
Category	Single Row Ball Bearings
Inventory	0.0
Manufacturer Name	NSK
Minimum Buy Quantity	N/A
Weight / Kilogram	4.1
EAN	0029176034503
Product Group	B00308
Enclosure	Open



Industry Parts Online

Precision Class	ABEC 1 ISO P0
Maximum Capacity / Filling Slot	No
Rolling Element	Ball Bearing
Snap Ring	No
Internal Special Features	No
Cage Material	Steel
Internal Clearance	C0-Medium
Inch - Metric	Metric
Long Description	150MM Bore; 225MM Outside Diameter; 35MM Outer Race Width; Open; Ball Bearing; ABEC 1 ISO P0; No Filling Slot; No Snap Ring; No Internal Special Features; C0-Medium Internal Clearance; Steel Cage
Other Features	Deep Groove
Category	Single Row Ball Bearing
UNSPSC	31171504
Harmonized Tariff Code	8482.10.50.68
Noun	Bearing
Keyword String	Ball
Manufacturer URL	http://www.nskamericas.com
Weight / LBS	9.3492
Inner Race Width	0 Inch 0 Millimeter
Outer Race Width	1.378 Inch 35 Millimeter
Bore	5.906 Inch 150 Millimeter
Outside Diameter	8.858 Inch 225 Millimeter
SRI	11.5
hidYobi	6030
LangID	1
D_	225



Industry Parts Online

SREX	0.04
B_	35
da min	161
hidTable	ecat_NSRDGB
Oil rpm	3000
SRE	11.5
mass	4.24
GRS rpm	2600
ra	2
SRIX	0.04
D_a	214
SRIN	-0.04
C0	126
fo	15.9
SREN	-0.04
DE_	209.725
Prod_Type3	DGBB_SR_OT
DA_	22.225
bomp	0
Z_	16
yobi	6030
C_conv	126000
ALPHA_	0
SDM_	187.5
r	2.1
KBRG	6101
SBRG	10
DI_	165.275